DESIGN NOTES:


- CONCRETE SHALL HAVE A 28 DAY MINIMUM COMPRESSIVE STRENGTH OF 5000 PSI
- SOIL UNIT WEIGHT DRY - 110 lbs/cu.ft.
- EQUIVALENT LATERAL PRESSURE DRY - 40 lbs/cu.ft.
- SOIL UNIT WEIGHT WET - 120 lbs/cu.ft.
- EQUIVALENT LATERAL PRESSURE WET - 80 lbs/cu.ft.
- MIX DESIGN MUST BE IN ACCORDANCE WITH NV ENERGY RS-G2 & RS-G4

PRODUCTION NOTES:

- THIS PRODUCT SHALL ONLY BE PRODUCED IN A JENSEN PRECAST FACILITY
- LIFTING INSERTS SHALL BE INSTALLED PER MANUFACTURER'S REQUIREMENTS
- APPLIED FINISH - NONE
- INTERNAL LINER/COATING - NONE
- EXTERNAL LINER/COATING - NONE

BILL OF MATERIALS


ITEM	UNIT QTY	QTY	PART NUMBER	DESCRIPTION
1	7.117 ft^3	7.117 ft^3	100011425	CONCRETE MIX GENERIC 5000 PSI
2	1	4	100002766	Insert Ferrule Loop 0.625 x 3.5" Zinc (F42 or Equiv.)
3	1	1	100019426	REINFORCING MAT 100019426



ISO VIEW

LIFTING NOTES
■ THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 2 LIFTING POINTS AT A MINIMUM 60° SLING ANGLE, MEASURED FROM HORIZONTAL.
*All rigging shall be design by a qualified professional. Loading diagrams show illustrations of possible rigging setups to achieve the required sling angle and load leg equalization. Other valid rigging configurations are possible. A qualified professional must be consulted prior to lifting.

RIGGING DIAGRAM*	B



BURY DEPTH:	0.0' - 3.0' to Top		
WATER LEVEL:	5.0'	APPROX. WEIGHT:	1070.61 Lbs
DESIGN SPEC:	ACI 318,ASTM C857	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Insert

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM


©2025 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.
This product shall only be produced in a Jensen Precast facility.

CHANGE HISTORY


NO.	DESCRIPTION	DATE	BY
1	2405-56948	12/18/24	KS
2			
3			

DESCRIPTION:	Riser 3684x12 NV Energy RS-82 CASTING LAYOUT		REV: A-3
PART NUMBER:	100001254	DRAWN BY:	K. Steinhorst
CREATED:	12/18/2024	MODIFIED:	1/16/2025
			SHEET: 1 OF 2


100001254.idw




PLAN VIEW



SECTION A-A



SECTION B-B



SECTION C-C



SECTION D-D

BURY DEPTH:	0.0' - 3.0' to Top		
WATER LEVEL:	5.0'	APPROX. WEIGHT:	1070.61 Lbs
DESIGN SPEC:	ACI 318,ASTM C857	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Insert

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2025 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.
This product shall only be produced in a Jensen Precast facility.

DESCRIPTION:	Riser 3684x12 NV Energy RS-82 CASTING DRAWING		REV: A-3
PART NUMBER:	100001254	DRAWN BY:	K. Steinhorst
CREATED:	12/18/2024	MODIFIED:	1/16/2025

SHEET: 2 OF 2

100001254.idw