
NOTES
■ FOR COMPLETE DESIGN AND PRODUCT INFORMATION CONTACT JENSEN PRECAST.



ISO LAYOUT

BILL OF MATERIALS

ITEM	QTY	PART NUMBER	DESCRIPTION
1	70.633 ft^3	100011425	CONCRETE MIX GENERIC 5000 PSI
2	160.000 in	100024619	STRUT C-CHANNEL CONCRETE INSERT 1-5/8 X 1-5/8 12GA W/ANCHORS GALV
3	2	100005928	INSERT FERRULE LOOP 1/4 X 2-3/4 PLATED F42
4	2	100005931	GROUND INSERTS BOTTLE ROCKET BRASS 1/4X16 STEEL ROD 12D69
5	2	100007387	1/2" GROUND INSERT WIRE ROPE CLAMP GALV
6	2	100004658	PULL IRON OFFSET .875DIA 7.375IH X 9L X 13.75W GALV
7	4	100002874	ANCHOR DOGBONE P52 4T X 4-3/4" GALV
8	2	100007133	ANCHOR UTILITY .671DIA 7.625-SLAB GALV P75 8UA671
9	40	100003013	TERMINATOR DUCT WITH SEAL 4.35IN T4350
10	40	100019623	TERMINATOR DUCT EXTENSION 4X2 TBE4X2
11	10	100012720	INSERT PLASTIC W/ BREAK OFF SNAP 0.5IN
12	10	100007441	STRUT FITTING SPRING NUT 1/2-13 UNC 1-5/8 CHANNEL REGULAR SPRING ZINC
13	10	100002583	CABLE RACK CORNER SUPPORT 18 X 18 10A56 GALV
14	8	100002525	CABLE RACK 14 HOLE GALV TABS
15	1.000 gal	100006420	COATING PAINT LATEX WHITE
16	40	100008814	WASHER FLAT 1/2 REGULAR TYPE A GALV
17	30	100034614	HEX BOLT 1/2-13 UNC 1.5 GALV
18	10	100007007	HEX NUT 1/2-13 UNC HEAVY GALV
19	1	300125241	REINFORCING MAT 300125241

100004505.idw

LIFTING NOTES
■ DEMOLDING: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINTS AT A MINIMUM 60° SLING ANGLE, MEASURED FROM HORIZONTAL.
■ INSTALLATION: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2500 PSI WITH 2 LIFT CONNECTIONS EQUALLY LOADED TO 2 LIFTING POINTS AT A MINIMUM 60° SLING ANGLE, MEASURED FROM HORIZONTAL.

REVISION HISTORY			
REV	DESCRIPTION	DATE	BY
A	DRAWING CREATED	7/7/2020	MRV


BURY DEPTH:	0.8' - 5.0' to Top of Top Slab		
WATER LEVEL:	3.5'	APPROX. WEIGHT:	10741.34 Lbs
DESIGN SPEC:	ASTM C857,ACI 318	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	A-Anchor

JENSEN PRECAST EST. 1968


WWW.JENSENPRECAST.COM

©2021 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.


DESCRIPTION:	Tunnel Vault 72W x 108H x 24L AT&T Int. Coating - White Latex Paint CASTING LAYOUT		REV: A-1
PART NUMBER:	100004505	DRAWN BY:	M.Vallarino
CREATED:	7/6/2020	MODIFIED:	3/3/2021
			SHEET: 1 OF 2




PLAN VIEW




SECTION A-A



SECTION B-B



SECTION C-C



SECTION D-D

BURY DEPTH:	0.8' - 5.0' to Top of Top Slab		
WATER LEVEL:	3.5'	APPROX. WEIGHT:	10741.34 Lbs
DESIGN SPEC:	ASTM C857,ACI 318	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	A-Anchor

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2021 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

DESCRIPTION:	Tunnel Vault 72W x 108H x 24L AT&T Int. Coating - White Latex Paint CASTING DRAWING		REV: A-1
PART NUMBER:	100004505	DRAWN BY:	M.Vallarino
CREATED:	7/6/2020	MODIFIED:	3/3/2021
			SHEET: 2 OF 2

100004505.idw