NOTES
■ ALL PARTS TO BE STENCILED: MFG DATE / JOB NUMBER / PRODUCT ID / WEIGHT.

BILL OF MATERIALS

ITEM	UNIT QTY	QTY	PART NUMBER	DESCRIPTION
1	5.556 ft^3	5.556 ft^3	100024079	CONCRETE #19 MOD SCC
2	1	8	100002867	ANCHOR DOGBONE P52 2T X 3-3/8" GALV
3	1	1	300127004	REINFORCING MAT 300127004



PLAN VIEW



SECTION A-A



SECTION B-B



SECTION C-C



SECTION D-D

LIFTING NOTES
■ DEMOLDING: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2,500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINTS AT A MINIMUM 90° SLING ANGLE, MEASURED FROM HORIZONTAL.
■ INSTALLATION: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 5,500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINTS AT A MINIMUM 90° SLING ANGLE, MEASURED FROM HORIZONTAL.

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
B-1	REVISED TONGUE & GROOVE, REMOVED TAG	6/20/2023	

BURY DEPTH:	1.0' - 2.0' to Top		
WATER LEVEL:	3.0'	APPROX. WEIGHT:	838.11 Lbs
DESIGN SPEC:	ACI 318,ASTM C857	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Dogbone

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2023 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

DESCRIPTION:	Riser 4878x6 CASTING LAYOUT		REV: B-1
PART NUMBER:	100012207	DRAWN BY:	J. Prado
CREATED:	3/2/2021	MODIFIED:	6/20/2023
			SHEET: 1 OF 1

100012207.idw