

NOTES
■ ALL PARTS TO BE STENCILED: MFG DATE / JOB NUMBER / PRODUCT ID / WEIGHT.

BILL OF MATERIALS


ITEM	UNIT QTY	QTY	PART NUMBER	DESCRIPTION
1	17.472 ft^3	17.472 ft^3	100006029	CONCRETE 5500 PSI SCC ED
2	1	4	100002867	ANCHOR DOGBONE P52 2T X 3-3/8" GALV
3	1	2	100006081	STRUT C-CHANNEL CONCRETE INSERT 1-5/8 X 1-5/8 12GA W/ANCHORS N-3200 10IN GALV
4	1	6	100008114	INSERT THREADED METAL 1/2-13 UNC 1-1/2 IN OPEN
5	1	1	100017998	REINFORCING MAT 100017998




PLAN VIEW



ELEVATION A-A



SECTION B-B



DETAIL C

LIFTING NOTES
■ DEMOLDING: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINTS AT A MINIMUM 90° SLING ANGLE, MEASURED FROM HORIZONTAL.
■ INSTALLATION: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 5500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINTS AT A MINIMUM 90° SLING ANGLE, MEASURED FROM HORIZONTAL.

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
B-1	UPDATE B.O.M.	8/1/2023	

BURY DEPTH:	-0.3' - -0.3' to Top of Top Slab		
WATER LEVEL:	3'	APPROX. WEIGHT:	2631.83 Lbs
DESIGN SPEC:	ASTM C857,ACI 318	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Dogbone

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2023 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

DESCRIPTION:	Pad 72102x6 EDISON UGS SS530, SB-1 CASTING LAYOUT		REV: B-2
PART NUMBER:	100012277	DRAWN BY:	D. Mejia
CREATED:	2/20/2018	MODIFIED:	8/1/2023
			SHEET: 1 OF 1

100012277.idw