NOTES
■ ALL PARTS TO BE STENCILED: MFG DATE / JOB NUMBER / PRODUCT ID / WEIGHT.

BILL OF MATERIALS

ITEM	UNIT QTY	QTY	PART NUMBER	DESCRIPTION
1	5.257 ft^3	5.257 ft^3	100005993	CONCRETE 5500 PSI DRYCAST MIX
2	1	4	100002867	ANCHOR DOGBONE P52 2T X 3-3/8" GALV
3	1	1	100018103	REINFORCING MAT 100018103



PLAN VIEW



SECTION A-A



SECTION B-B



DETAIL E
JOIN DETAIL



SECTION C-C



SECTION D-D

LIFTING NOTES
■ DEMOLDING: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2,500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINT AT A MINIMUM 60° SLING ANGLE, MEASURED FROM HORIZONTAL.
■ INSTALLATION: THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 5,500 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 4 LIFTING POINT AT A MINIMUM 60° SLING ANGLE, MEASURED FROM HORIZONTAL.

BURY DEPTH:	0.0' - 5.0' to Top		
WATER LEVEL:	3.0'	APPROX. WEIGHT:	791.64 Lbs
DESIGN SPEC:	ACI 318,AASHTO LRFD	LOADING SPEC:	AASHTO HL-93
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Dogbone

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2022 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
C-1	REVISED DESCRIPTION	11/16/2022	

DESCRIPTION:	Riser 4848x6 LADWP 1-802 G-1B CASTING LAYOUT		REV: C-1
PART NUMBER:	100012395	DRAWN BY: J. Prado	SHEET: 1 OF 1
CREATED:	1/3/2019	MODIFIED: 11/16/2022	

100012395.idw