

NOTES
■ MINIMUM EXCAVATION SIZE: 16'-11" X 5'-11" DEPTH REQ'D.
■ FOR COMPLETE DESIGN AND PRODUCT INFORMATION CONTACT JENSEN PRECAST.

BILL OF MATERIALS

ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	200028997	Tank JP 2000 Gallon 6 Inch Rect. Bottom Section Single Baffle
2	1	200014301	Tank JP 2000 Gallon x 5 Slab Top 24 ECE
3	1	200026722	Vertical Slab Baffle JP 2000
4	3	100013648	SEALANT JOINT BUTYL RUBBER ASTM C-990 AND M198 CS-102 1IN EQUIV X14.5FT PER ROLL



ISO LAYOUT



SECTION

200029092.idw

LIFTING NOTES
■ THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2500 PSI WITH 2 LIFT CONNECTIONS EQUALLY LOADED TO 2 LIFTING POINTS AT A MINIMUM 90° SLING ANGLE, MEASURED FROM HORIZONTAL.

REVISION HISTORY			
REV	DESCRIPTION	DATE	BY
A	DRAWING CREATED	8/19/2019	T.Larson
B	BASE LIFTING UPDATED; TOP SLAB NOTCHES & REBAR UPDATED	4/27/2020	T.Larson
C	TOP SLAB LIFTING UPDATED AND GROOVE ADDED	2/9/2021	T.Larson

BURY DEPTH:	1.1' - 6.0' to Top of Top Slab		
WATER LEVEL:	Below Structure	WEIGHT:	20175.68 Lbs
DESIGN SPEC:	ASTM C890,ACI 318	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:		LIFTING TYPE:	Cable

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2018 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

DESCRIPTION:	Tank JP 2000 Gallon 6 Inch Assembly ECE Double Baffle LAYOUT REVIEW		REV: C-1
PART NUMBER:	200029092	DRAWN BY:	T.Larson
CREATED:	1/31/2019	MODIFIED:	2/9/2021
			SHEET: 1 OF 1