DESIGN NOTES:


- CONCRETE SHALL HAVE A 28 DAY MINIMUM COMPRESSIVE STRENGTH OF 6000 PSI
- SOIL UNIT WEIGHT DRY - 110 lbs/cu.ft.
- EQUIVALENT LATERAL PRESSURE DRY - 40 lbs/cu.ft.
- SOIL UNIT WEIGHT WET - 120 lbs/cu.ft.
- EQUIVALENT LATERAL PRESSURE WET - 80 lbs/cu.ft.

PRODUCTION NOTES:

- THIS PRODUCT SHALL ONLY BE PRODUCED IN A JENSEN INFRASTRUCTURE FACILITY
- LIFTING INSERTS SHALL BE INSTALLED PER MANUFACTURER'S REQUIREMENTS
- APPLIED FINISH - BROOMED
- INTERNAL LINER/COATING - NONE
- EXTERNAL LINER/COATING - NONE

BILL OF MATERIALS


ITEM	UNIT QTY	QTY	PART NUMBER	DESCRIPTION
1	29.962 ft^3	29.962 ft^3	100011427	CONCRETE MIX GENERIC 6000 PSI
2	1	1	200079784	CAB2-3370-CH4-DP-G-SL-OH09
3	1	4	100044113	ANCHOR RAPID LIFT TECH 5T CLUTCH 4.4375IN LONG MB RL-25 GALV
4	1	1	300153796	REINFORCING MAT 300153796
5	1	1	300153831	REINFORCING MAT 300153831



ISOMETRIC VIEW

LIFTING NOTES
■ THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 3000 PSI WITH 4 LIFT CONNECTIONS EQUALLY LOADED TO 2 LIFTING POINTS AT A MINIMUM 60° SLING ANGLE, MEASURED FROM HORIZONTAL.
*All rigging shall be design by a qualified professional. Loading diagrams show illustrations of possible rigging setups to achieve the required sling angle and load leg equalization. Other valid rigging configurations are possible. A qualified professional must be consulted prior to lifting.

RIGGING DIAGRAM*	B



BURY DEPTH:	0.0' - 0.0' to Top		
WATER LEVEL:	Below Structure	APPROX. WEIGHT:	4854.68 Lbs
DESIGN SPEC:	ACI 318,ASTM C857	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Tech Erection Anchor

Infrastructure
JENSEN
WWW.JENSENINFRASTRUCTURE.COM


©2026 Jensen Infrastructure - All rights reserved.
All materials appearing as Jensen Infrastructure documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Infrastructure , any use of Jensen Infrastructure work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.
This product shall only be produced in a Jensen Infrastructure facility.

CHANGE HISTORY


NO.	DESCRIPTION	DATE	BY
A	DRAWING CREATED	2/23/2023	E.Fine
B	REPLACED HATCH COVER	7/9/2026	A.Viveiros
C	UPDATED BONDING BAR BOM LEVEL	9/18/2026	SB

DESCRIPTION:	Vault 7296x9 Slab Top 33"x70"C Cast-In Frame Tacoma Power 63355 STD CASTING LAYOUT		REV: B-1
PART NUMBER:	200072913	DRAWN BY:	E.Fine
CREATED:	2/22/2023	MODIFIED:	9/24/2026
			SHEET: 1 OF 3


200072913.idw




PLAN VIEW



PLAN VIEW
(SHOWING LIFTING)



VIEW A-A



VIEW B-B

BURY DEPTH:	0.0' - 0.0' to Top		
WATER LEVEL:	Below Structure	APPROX. WEIGHT:	4854.68 Lbs
DESIGN SPEC:	ACI 318,ASTM C857	LOADING SPEC:	A-16 (AASHTO HS20-44)
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Tech Erection Anchor


Infrastructure
JENSEN
WWW.JENSENINFRASTRUCTURE.COM

©2026 Jensen Infrastructure - All rights reserved.
All materials appearing as Jensen Infrastructure documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Infrastructure , any use of Jensen Infrastructure work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.
This product shall only be produced in a Jensen Infrastructure facility.


DESCRIPTION:	Vault 7296x9 Slab Top 33"x70"C Cast-In Frame Tacoma Power 63355 STD CASTING DRAWING		REV: B-1
PART NUMBER:	200072913	DRAWN BY:	E.Fine
CREATED:	2/22/2023	MODIFIED:	9/24/2026

SHEET: 2 OF 3

200072913.idw



PLAN VIEW
(SHOWING BONDING BAR(S)
AND HATCH FOR CLARITY)



BONDING DETAIL

200072913.idw

BURY DEPTH:	0.0' - 0.0' to Top			DESCRIPTION: Vault 7296x9 Slab Top 33"x70"C Cast-In Frame Tacoma Power 63355 STD CASTING DRAWING	REV: B-1
WATER LEVEL:	Below Structure	APPROX. WEIGHT:	4854.68 Lbs		
DESIGN SPEC:	ACI 318,ASTM C857	LOADING SPEC:	A-16 (AASHTO HS20-44)		SHEET: 3 OF 3
REINFORCEMENT TYPE:	Rebar	LIFTING TYPE:	Tech Erection Anchor	PART NUMBER: 200072913 / DRAWN BY: E.Fine	
				CREATED: 2/22/2023 / MODIFIED: 9/24/2026	

Infrastructure
JENSEN
WWW.JENSENINFRASTRUCTURE.COM

©2026 Jensen Infrastructure - All rights reserved.
All materials appearing as Jensen Infrastructure documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Infrastructure , any use of Jensen Infrastructure work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.
This product shall only be produced in a Jensen Infrastructure facility.