| NOTES |
|---|
| ■ FOR COMPLETE DESIGN AND PRODUCT INFORMATION CONTACT JENSEN PRECAST. |

## BILL OF MATERIALS

| ITEM | QTY | PART NUMBER | DESCRIPTION |
|---|---|---|---|
| 1 | 6.932 ft^3 | 100002728 | CONCRETE MIX GENERIC 4000 PSI |
| 2 | 1 | 100020495 | WWR REINFORCING CAGE 100020495 |
| 3 | 2 | 100007385 | INSERT EZ LIFT PIN THREADED PLASTIC SOCKET LANE |
| 4 | 2 | 100005708 | LIFT PINS EZ SCREW IN 1-1/2 |

| ALTERNATE REINFORCING OPTIONS | |
|---|---|
| PART NUMBER | DESCRIPTION |
| 200042555 | BAR REINFORCING CAGE 200042555 |
| 200042556 | MBK WIRE REINFORCING CAGE 200042556 |

200080408.idw




ISOMETRIC VIEW

| LIFTING NOTES |
|---|
| ■ THIS CONCRETE PRODUCT IS DESIGNED TO BE LIFTED AT 2500PSI WITH 2 LIFT CONNECTIONS EQUALLY LOADED TO 2 LIFTING POINTS AT A MINIMUM 45°, MAXIMUM 90° SLING ANGLE, MEASURED FROM HORIZONTAL. |

| | | | |
|---|---|---|---|
| BURY DEPTH: | 0.0' - 99.0' to Top | | |
| WATER LEVEL: | 0.0' | WEIGHT: | 1042.88 Lbs |
| DESIGN SPEC: | ASTM C478 | LOADING SPEC: | A-16 (AASHTO HS20-44) |
| REINFORCEMENT TYPE: | WWR Plain | LIFTING TYPE: | SP Socket |


JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM


©2019 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

| REVISION HISTORY | | | |
|---|---|---|---|
| REV | DESCRIPTION | DATE | BY |
| 1 | 2308-55796 | 9/27/2023 | APS |

| | | | | |
|---|---|---|---|---|
| DESCRIPTION: Stand Pipe D3644x24 GU<br>CASTING LAYOUT | | | | REV: A-2 |
| PART NUMBER: | 200080408 | DRAWN BY: | A.Sprung | SHEET: 1 OF 2 |
| CREATED: | 9/21/2023 | MODIFIED: | 10/11/2023 | |




PLAN VIEW




ELEVATION

| | | | |
|---|---|---|---|
| BURY DEPTH: | 0.0' - 99.0' to Top | | |
| WATER LEVEL: | 0.0' | WEIGHT: | 1042.88 Lbs |
| DESIGN SPEC: | ASTM C478 | LOADING SPEC: | A-16 (AASHTO HS20-44) |
| REINFORCEMENT TYPE: | WWR Plain | LIFTING TYPE: | SP Socket |

JENSEN PRECAST EST. 1968

WWW.JENSENPRECAST.COM

©2019 Jensen Precast- All rights reserved.
All materials appearing as Jensen Precast documents and the like are proprietary work product and are protected under U.S. copyright and other laws.
Unless in conjunction with business conducted with Jensen Precast, any use of Jensen Precast work product without express, written consent is prohibited, and recipient is prohibited from distributing any and all work product to non-approved third parties under penalty of civil action.

| | | | |
|---|---|---|---|
| DESCRIPTION: | Stand Pipe D3644x24 GU<br>CASTING DRAWING | | REV: A-2 |
| PART NUMBER: | 200080408 | DRAWN BY: | A.Sprung |
| CREATED: | 9/21/2023 | MODIFIED: | 10/11/2023 |
| | | | SHEET: 2 OF 2 |

200080408.idw